LOCAL AIR-CONDITIONERS



REMKO MKT 251/291 S-LINE

Ready to use anytime, anywhere - no installation needed

The MKT Series mobile air conditioner is ideal if you need a flexible air-conditioning solution. The *S-LINE* series convinces with its modern optics in a trendy silver colour. This unit, with its four wheels and flexible air outlet hose, can be used anywhere. You just need a place to plug it in. Its high cooling capacity ensures that heat remains outside. All functions are controlled electronically.

- High cooling capacity
- Ready for immediate operation
- Digital display of temperature and timer time
- Programmable timer function for activation and deactivation times
- Lightweight, requiring minimum space for setup

- Removable air filter
- 3 fan speeds
- With infrared remote control in standard design
- Automatic condensate removal
- Compact design
- Display of operating state via LED

Technical data

Unit type		MKT 251	MKT 291
Cooling capacity	kW	2.6	2.9
Energy efficiency class		Α	A
Energy efficiency size EER		2.6	2.6
Energy consumption, hourly	kWh	0.99	1.11
Refrigerant 2)		R410A	R410A
Basic filling volume / CO2 equivalent	kg/t	0.50/1.04	0.65/1.36
Fan speeds		3	3
Max. air flow rate	m³/h	320	320
Max. dehumidification capacity	l/h	1.6	1.8
Usage area (room size) approx.	m³	80	90
Sound pressure level per speed LpA 1)	dB(A)	49/52/53	49/53/54
Max. sound power	dB(A)	62	64
Voltage supply	V/Ph/Hz	230/1~/50	230/1~/50
Power consumption	kW	0.99	1.11
Air outlet tube, length	mm	1500	1500
Air outlet tube Ø	mm	150	150
Dimensions - height/width/depth	mm	770/435/430	770/435/430
Weight	kg	33.0	33.0
Compact unit		4.642255	4.642205
Ref. no. colour: white		1612255	1612295
Ref. no. colour: silver		1612256	1612296
¹⁾ At distance of 1 m in the open air ²⁾	GWP = 2088		
Accessories			



Wall lead-through for air outlet tube



1613115



1613115





REMKO RKL 300/360 S-LINE

High-performance spot cooler

Working and living areas can be cooled in a targeted manner using the mobile air conditioners RKL 300 and RKL 360. The *S-LINE* series convinces with its modern optics in a trendy silver colour. The condenser, compressor, and evaporator reside in a compact housing in the case of these small, flexible air-conditioners.

- High cooling capacity
- Ready for immediate operation
- Easy and efficient automatic dehumidification
- Practical electronic system for operation with digital display of temperature and other operating modes
- Air discharge with swing function

- Removable air filter
- Gradually adjustable air outlet direction
- Automatic condensate removal
- Compact design
- With infrared remote control in standard design
- Programmable 24-hour timer function

Technical data

Unit type		RKL 300	RKL 360
Cooling capacity	kW	3.2	3.6
Energy efficiency class		Α	Α
Energy efficiency size EER		2.8	2.7
Energy consumption, hourly	kWh	1.13	1.33
Refrigerant 2)		R410A	R410A
Basic filling volume / CO2 equivalent	kg/t	0.70/1.46	0.70/1.46
Fan speeds		3	3
Max. air flow rate	m³/h	450	450
Max. dehumidification capacity	l/h	2.0	2.1
Usage area (room size) approx.	m³	90	100
Sound pressure level per speed LpA 1)	dB(A)	49/51/53	49/51/53
Max. sound power	dB(A)	61	61
Voltage supply	V/Ph/Hz	230/1~/50	230/1~/50
Power consumption	kW	1.13	1.33
Air outlet tube, length	mm	1500	1500
Air outlet tube Ø	mm	140	140
Dimensions - height/width/depth	mm	840/450/380	840/450/380
Weight	kg	35.0	35.0
Compact unit			
Ref. no. colour: white		1615300	1615360
Compact unit S-LINE			
Ref. no. colour: silver		1615301	1615361







